


European and American Television Cameras

	Make	BTS
	Model	LDK 910
	Country	Germany
	Camera Type : Compact Studio colour, full facilities.	
	Camera Description : Small square camera with viewfinder on top, prominent wrap-around carrying handles. Large cue lights on viewfinder	

Data	Data
Tube details 3 x FT5 NXA1100 CCDs. 806pxls.	Line standards 625/50 525/60
Lens details Zoom	Colour standards PAL/NTSC/SECAM
Sig. to Noise 60dB PAL normal gain	Drives or locking Genlock
Sensitivity 2000Lux @F4.0 PAL	Weight * 18Kg.
Resolution > 700 lines	Colours Beige
Viewfinder 7 inch, tilts and rotates.	Dimensions * 300H x 240W x 260L mm.
Camera cable Triax, 14mm Ø to 2000m.	Date introduced 1989
Power supply 110-120/220-240v. 47-63Hz. 280W.	

*Excluding Lens & Viewfinder

Associated equipment

Base station is 3U high and has no operational controls, The OCP has all the controls for the camera and a small control panel has iris, lift and colour paint controls. The LDK91 is the portable companion.

Features

Compatible with the LDK900 system.
 In transit the viewfinder fits in front of the camera in place of the lens.
 The Triax system is based on the Philips LDK6 system with full bandwidth R, G, B signals.
 Claimed to be "Rugged, reliable and rain proof".

General description

There is only one program microphone circuit from the camera head.
 There is a teleprompter circuit to the camera and a 70VA utility power output.

References

SMPTE, March 1991 page 167

Innovations

Viewfinder character display.

History

Developed from the LDK900 & LDK91

Notes



Rear View of LDK910 camera